



## Seminar 21

Uncertainties in Compressor Performance and Field  
Performance of Liquid-Chilling Systems

# An introduction to field testing of liquid chillers and ASHRAE Standard 184

Ian Spanswick

O2RC Solutions LLC

[ian.spanswick@o2rc.com](mailto:ian.spanswick@o2rc.com)

+1 713 447 5618

# Learning Objectives

- Understand the challenges to conducting a field performance test of a liquid chiller compared to a manufacturer's test at the factory.
- Understand the purpose & scope of ASHRAE Standard 184.
- Understand the key features of the ASHRAE Standard 184 Workbook.

*ASHRAE is a Registered Provider with The American Institute of Architects Continuing Education Systems. Credit earned on completion of this program will be reported to ASHRAE Records for AIA members. Certificates of Completion for non-AIA members are available on request.*

*This program is registered with the AIA/ASHRAE for continuing professional education. As such, it does not include content that may be deemed or construed to be an approval or endorsement by the AIA of any material of construction or any method or manner of handling, using, distributing, or dealing in any material or product. Questions related to specific materials, methods, and services will be addressed at the conclusion of this presentation.*

# Acknowledgements

Past and present members of ASHRAE SPC-184.

The University of Maryland Facilities Department  
for the Beta test site for the Uncertainty Calculation  
Spreadsheet.

## Outline/Agenda

- Purpose of ASHRAE Standard-184.
- Scope of ASHRAE Standard-184.
- What measurements are required for a test.
- Challenges of field-testing liquid chillers.
- Combining measurements to characterize chiller performance.
- Introducing the ASHRAE Standard-184 workbook.

# Purpose of ASHRAE Standard-184

- The industry has published standards that address **factory performance testing** of liquid chillers.
  - ASHRAE 30 / AHRI 550/590 (electric) or 560 (absorption) covers many common chiller configurations.
  - If new equipment performance verification is desired, then a factory test can be performed under controlled conditions.
  - Covers the majority of chillers sold, but not all.
- The industry did **not have** a published standard that addresses the **field performance testing** of liquid chillers.
  - In most cases it is not possible to apply a factory testing standard to field installations where instrument accuracies and installation locations may not be optimal.
- ASHRAE 184, first published in 2016
  - Covers field performance testing.

# Scope of ASHRAE Standard-184

This standard includes the following:

- Types of liquid-chilling systems.
  - Vapor compression cycle.
  - Absorption cycle.
  - Water cooled, air cooled, heat recovery, etc
  - Chillers that cannot be factory tested.
- Any energy source
  - Electricity
  - Steam / hot water
  - Gas
  - Waste heat
- Does not include systems with a net refrigeration capacity less than 10 tonR [35 kW].


## Scope of ASHRAE Standard-184

- This standard **does not include a specification of standardized test conditions** under which the liquid-chilling system must operate.
  - Test conditions typically reflect the expected operating conditions and **are customer specified**.
  - They maybe the original design conditions but don't have to be.
- Plant can be in any condition:
  - Any chilled water temperature, design or otherwise
  - Any cooling water / ambient temperature, design or otherwise
  - Any percentage load,
  - Clean or fouled heat exchangers,
  - etc..
- For an effective test the chiller operation should be “stable”.



# What measurements might need to be taken?

Example:  
Water cooled  
electrically  
powered  
Chiller  
(with the  
optional  
heat recovery)





# What measurements might need to be taken?

ID / Tag #	Description of Measurement
FT-11	Evaporator liquid flow
TT-12	Evaporator inlet temperature
PDT-13	Evaporator pressure difference
TT-14	Evaporator outlet temperature
FT-21	Condenser liquid flow
TT-22	Condenser inlet temperature
PDT-23	Condenser pressure difference
TT-24	Condenser outlet temperature
No ID	Power consumption for the Chiller, including any auxiliary systems included in the test boundary and includes voltage balance measurement.
	If heat recovery is included:
FT-81	Heat recovery condenser liquid flow
TT-82	Heat recovery condenser inlet temperature
PDT-83	Heat recovery condenser difference
TT-84	Heat recovery condenser outlet temperature

# Challenges of field-testing liquid chillers.

- Performance measurement requires measuring several parameters and combining these
  - Capacity result;  $\text{kW}_R$ , tonR, Btu/hr, etc.
  - Performance result; COP,  $\text{kW}/\text{tonR}$ , EER, etc.
- **Nothing about measurement is certain....**
  - Need to characterize uncertainty
  - eg  $932 \pm 5.2 \text{ kW}_R$ ,  $1,050 \pm 32.4 \text{ tonR}$ ,  $5.21 \pm 0.45 \text{ COP}$ .
- Two basic types of uncertainty
  - Random
  - Systematic

# Challenges of field-testing liquid chillers.

- **Random** is the variation in the actual measurement

- “Real” variation in the measured values
- Plant operational stability

This is what it is....  
Can only try to stabilize  
operation during testing

- **Systematic** is the accuracy of the measuring system / devices

- Calibration accuracy of the device
- Device accuracy
  - Eg 0.2%
- A to D resolution of the data logger
- Non-ideally installed device
  - Flow transmitter not installed with required up and downstream straight lengths. Workbook provides some assistance here...
  - Temperature stratification leaving an evaporator

The most challenging  
characterizations to  
determine.

## Combining measurements to develop a conclusion.

COP derived from (for example)

$$\text{COP} = \frac{\text{Gross evaporator capacity}}{\text{Total input power}}$$

$$= \frac{m \cdot c_p \cdot \Delta T + m \cdot \Delta P / \rho}{\sum W}$$

But mass flow is not typically measured directly, volume flow is:

$$= \frac{V \cdot \rho \cdot c_p \cdot \Delta T + V \cdot \Delta P}{\sum W}$$

There might be more than one power source...

Even measuring power usually involves current transformers.

- All measurement devices involve uncertainty
  - Don't forget this extends to the recording device / data-logger which is itself has a discrete accuracy:
    - Analog to Digital eg 12 bit =  $1/2^{12} = 1/4096 = 0.00024$ .

## Introducing the ASHRAE Standard-184 workbook.

- The mathematics behind calculating uncertainty can be challenging.
- In support of ASHRAE Standard 184 a workbook has been developed.
  - Published with Addendum A December 7 2018
- Aim is to provide an accessible working calculation of the methods included in the standard.
  - Leads the user through the required steps.
  - Provides an auditable workbook of the calculations.
- User selectable systems and configurations.
- Includes the pre-test estimates
  - Establish agreement of expected outcome prior to testing.

# Introducing the ASHRAE Standard-184 workbook.



# Workbook - Overview

## Tab color key

### Workbook Overview & Guide.

#### Workbook

This workbook is provided in support of ASHRAE Standard 184. It supports performance verification of the systems types outlined in the standard (electric water cooled only for this revision). Calculation of chiller the performance and associated uncertainty involves many steps. The intent of this workbook it to attempt to make this as approachable as possible. Although the workbook contains many worksheets (tabs) it is segregated into colored tabs to identify the function of each tab.

#### Tabs

Tabs are colored to assist with understanding of the function each tab serves

Gray Instructions & information, read only, no input required.

Red Primary configuration. Entry of the key configuration details of the system, including fluids and the units of measurement to be used.

Blue Input for each measurement point. One tab will need to be completed for each measurement position taken (e.g. evaporator water leaving temperature). Each tab allows for up to six index

Light blue Optional support input for instrument calibration. This feature allows any calibration information to be included in the final calculations.

Yellow Intermediary calculations. This is for information and review only.

Green Results summary

Purple Support information, read only, no input required. Fluid properties, unit conversions and workbook configuration information.

It should be noted that for each analysis only two colors (red & blue) of worksheet tabs require user input and a third color is optional (light blue).

#### Cells

**Note:** To assist with understanding where data entry is required only cells color coded with a cyan background need to be completed.

All other cells are protected and do not allow data entry.

#### Measurement tabs

The configuration of EACH measurement tabs is likely to be the most difficult task when using this workbook.

Each tab consists of three main areas (remember, only the blue cells need input):

**Pretest estimates for uncertainty information (shaded light yellow).**

This is where the expected / anticipated values for the actual test are entered.

These values work with the uncertainty information entered (below) to give an understanding of what the actual test results might achieve.

**Test measurement values (shaded light green).**

7		
8		
9	Random Standard Uncertainty	
10	Absolute	number of observations available for a single measur
11		number of degrees of freedom
12		sample mean
13		standard deviation of data sample

Revisions	Instructions	CheckList	Glossary	Input Configuration	Calibration Template	EvapFlow	EvapTempIn	EvapTempOut	EvapPd	CondFlow	CondTempIn	CondT
-----------	--------------	-----------	----------	---------------------	----------------------	----------	------------	-------------	--------	----------	------------	-------

Instructions and assistance

Test setup

Calibration

Measurement specific tabs



# Workbook – Input Configuration Tab

Set the system  
& testing  
Parameters

This tab first!

(ERW) Electric water cooled  
(SRW) Steam water cooled  
(GRW) Gas engine water cooled  
(HAW) Hot water absorption water cooled  
(SAW) Steam absorption water cooled  
(GAW) Gas absorption water cooled  
(ERA) Electric air cooled

This sets the visible tabs 😊

General	
Date of Test	19-Mar-2015
Unit Identification	123456789-0000
Remark 1	This is remark 1
Remark 2	This is remark 2
Remark 3	This is remark 3
Site Owner	
Testing agent	
Job Name	Worksheet Development
Uncertainty Confidence Level	95%
System Type	(ERW) Electric water cooled
Operating Mode	Cooling
Instrumentation	
Type of Flow Measurements	
Evaporator Liquid Flow	Volume
Condenser Liquid Flow	Volume
Hot Water	Volume
Steam	Volume
Gas (Fuel)	Volume
Input Power Measurements	
Number of Electrical Measurements	2
Units of Measurement	
Input	Temperature °F Length ft Pressure psig Pressure Differential ftH2O(at60°F) Volume Flow Rate gal/min Mass Flow Rate lbm/s Power kW Cooling capacity tonR Heating capacity tonR Density lbm/ft³ Specific Heat Capacity Btu/(lbm·Δ°F)
Output	Cooling efficiency kW/tonR Heating efficiency COP
Fluid Properties	
Evaporator (cold) Fluid	AHRI water properties
Condenser (hot) Fluid	AHRI water properties

Set the units of measurement  
& flow measurement type

Includes water properties  
Allows for input of other fluids

# Workbook – Measurement Tabs

One tab per measurement position

Only blue cells require input 😊

X = EvapFlow		Random uncertainties captured here				This measurement worksheet allows test setups ranging from a single measurement to six redundant measurement instruments that are averaged into one.						
Type	Volume Flow Rate											
Units	gal/min											
						Pre-Test Estimates	Test Measurement Values					
							Instrument Number $i = 1$ to $n$					
							1	2	3	4	5	6
Random Standard Uncertainty		Estimate	ISO Type	symbol	units							
Absolute	number of observations available for a single measurand (sample size)			N	-	100	333	0	0	0	0	
	number of degrees of freedom			$\nu_s$	-	99	332					
	sample mean			$\bar{X}$	gal/min	10800.0	10835.9					
	standard deviation of data sample			$s_X$	gal/min	108.0	60.9					
	random standard uncertainty of the mean of N observations of a measurand		Type A	$s_{\bar{X}}$	gal/min	10.80	3.34					
Relative	relative standard deviation			$\frac{s_X}{\bar{X}}$	-	1.00%	0.56%					
	relative random standard uncertainty			$\frac{s_{\bar{X}}}{\bar{X}}$	-	0.10%	0.03%					
Systematic Standard Uncertainty						Pre-Test Estimates	Test Measurement Values					
enter estimated systematic limits of error (expanded systematic uncertainty)							Instrument Number $i = 1$ to $n$					
Description		Distribution Type	Estimate ISO Type	Relative Variability	units		1					
Expanded	calibration residual error (bias error); if available use the expanded standard error of calibration	Normal	Type A	Low	gal/min	108.00	108.00					
	environmental influence (ambient temperature & pressure & humidity, analog signal)	Uniform	Type B	Medium	gal/min	27.00	27.00					
	spatial location or installation effect of measurement device (add specific examples for resolution)	Triangular	Type B	Low	gal/min	500.00	300.00					
	stability versus time (drift), depends on length of time since last calibration	Uniform	Type A	Low	gal/min	0.25	0.21					
	other [enter another source of systematic uncertainty]	Triangular	Type B	Medium	gal/min	14.00	14.00					
				High	gal/min							

Estimation of systematic uncertainties

- Provides worked examples of how to convert & combine instrument “accuracies”
- Includes suggestions for non-ideal flow installations

Pre-test

Test – up to 6 points

# Workbook – Measurement Tabs


Paste test data,  
up to 6 instruments

Estimate of  
A to D resolution


sample number (j)	time	Instrument Number					
		1	2	3	4	5	6
1	0:00:00	10941.1	#N/A	#N/A	#N/A	#N/A	#N/A
2	0:00:06	10753.7					
3	0:00:11	10747.4					
4	0:00:16	10851.7					
5	0:00:22	10780					
6	0:00:27	10805.7					
7	0:00:33	10774.3					
8	0:00:38	10775.8					
9	0:00:43	10745.7					
10	0:00:49	10867.2					
11	0:00:54	10825.8					
12	0:00:59	10761.3					
13	0:01:05	10728.3					
14	0:01:10	10835.3					
15	0:01:15	10773.2					
16	0:01:20	10773.7					
17	0:01:26	10805.3					
18	0:01:31	10798.1					
19	0:01:36	10718.7					
20	0:01:42	10759.8					
21	0:01:47	10884.1					
22	0:01:52	10899.1					
23	0:01:58	10850.6					
24	0:02:03	10852.3					
25	0:02:08	10924					
26	0:02:14	10768.8					

Estimate of the resolution from the trend log data					
1	2	3	4	5	6
0.21	#N/A	#N/A	#N/A	#N/A	#N/A

Pre-test and Test  
visualization of  
sample mean and  
associated  
uncertainty



Visualization of test data




# Workbook – Interim Results Tabs

Inputs		Pre-Test								Test						
		$i = 1 \text{ to } I$	1	2	3	4	5	6	7	8	1	2	3	4	5	6
Description			Evap liquid volume flow rate	Evap liquid density at flow meter	unused	unused	unused	unused	unused	unused	Evap liquid volume flow rate	Evap liquid density at flow meter	unused	unused	unused	unused
Symbol		-	V_ev	p_ev_in							V_ev	p_ev_in				
Units		-	gal/min	lbm/ft³							gal/min	lbm/ft³				
Nominal value		$\bar{X}_i$	10800	62.4147867							10835.9064	62.4156516				
Degrees of Freedom, Systematic Uncertainty		$(v_b)_i$	57.6630254	50							70.7906834	50				
Degrees of Freedom, Random Uncertainty		$(v_s)_i$	99	99							332	332				
Effective Degrees of Freedom		$(v_R)_i$	57.963056	50.0000015							70.8774121	50.0000004				
Absolute Systematic Standard Uncertainty		$b_{\bar{X}_i}$	211.797909	0.31207393							134.876541	0.31207826				
Absolute Random Standard Uncertainty		$s_{\bar{X}_i}$	10.8	3.8214E-05							3.33781736	1.8916E-05				
Absolute Combined Standard Uncertainty		$u_{\bar{X}_i}$	212.073087	0.31207394							134.917836	0.31207826				
Sensitivity Coefficient		$\theta_i$	8.34364336	1443.75							8.34375898	1448.54999				
Systematic Standard Uncertainty Contribution to the Combined Uncertainty of		$(\theta_i \cdot b_{\bar{X}_i})^2$	3122876.43	203001.377							1266474.18	204359.109				
Random Standard Uncertainty Contribution to the Combined Uncertainty of the Result		$(\theta_i \cdot s_{\bar{X}_i})^2$	8120.05509	0.00304389							775.619357	0.00075077				
Relative Systematic Contribution to the Standard Uncertainty of the Result		-	93.67%	6.09%							86.06%	13.89%				
Relative Random Contribution to the Standard Uncertainty of the Result		-	0.24%	0.00%							0.05%	0.00%				
Units for Conversion																
		Unit Numerator									gal	lbm				
		Unit Denominator									min	ft³				
Unit Conversion Calculation																
Mass	Length	Time	Temperature	Temperature Difference	Volume	Volume Flow Rate	Mass Flow Rate	Energy	Specific Energy	Power	Density	Specific Heat Capacity	HHV	Force	Pressure	
1	1	1	1	1	0.13368056	1	1	1	1	1	1	1	1	1	1	
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	
				Temperature		Volume Flow	Mass Flow		Specific			Specific Heat				
						Rate	Rate									
▶ ...	EvapPd	CondFlow	CondTempIn	CondTempOut	CondPd	PowerInput1	PowerInput2	Result_EvapMassFlowRate	Result_EvapTavg	Result_EvapΔT	Result_EvapNetCapacity ...	⊕	⋮	◀		

Results for Pre-test and Test

Pre-test and Test visualization



Interim results tabs

# Workbook – Final Results Tabs

Job Name	Worksheet Development							
Unit Identification	123456789-0000				Alternate Summary Results View			
Date of test	1-Jan-2019							
Starting Time of Test	12:00:00 AM							
Test Duration	30 minutes							
System Type	(ERW) Electric water cooled							
Remark 1	This is remark 1							
Remark 2	This is remark 2							
Remark 3	This is remark 3							
Number of Measurement Data Points	Between 333 and 333 points							
System Performance Summary								
Evaporator								
Evaporator Type	Flooded							
	Units of Measure	Test			Pre-Test			
		Average Value	Uncertainty Value	Relative Uncertainty	Average Value	Uncertainty Value	Relative Uncertainty	
Entering Fluid Temperature	°F	52.77	±0.24	±0.023%	53.00	±0.24	±0.023%	
Leaving Fluid Temperature	°F	42.01	±0.24	±0.023%	42.00	±0.24	±0.023%	
Fluid Temperature Difference	Δ°F	10.76	±0.33	±3.1%	11.00	±0.33	±3.0%	
Fluid Flow	gal/min	10840	±270	±1.2%	10800	±420	±2.0%	
Net Capacity	tonR	292500	±12000	±4.2%	298000	±16000	±5.2%	
Condenser								
Condenser Type	Water Cooled							
	Units of Measure	Test			Pre-Test			
		Average Value	Uncertainty Value	Relative Uncertainty	Average Value	Uncertainty Value	Relative Uncertainty	
Entering Fluid Temperature	°F	85.65	±0.24	±0.021%	85.00	±0.24	±0.022%	
Leaving Fluid Temperature	°F	94.55	±0.24	±0.021%	94.24	±0.24	±0.021%	
Fluid Temperature Difference	Δ°F	8.91	±0.33	±3.7%	9.24	±0.34	±3.7%	
Fluid Flow	gal/min	15110	±370	±1.1%	15250	±290	±0.89%	
Net Capacity	tonR	334800	±16000	±4.7%	350800	±15000	±4.3%	


## Summary for Pre-test and Test

Driver				
Driver Type	Electric Motor			
	Units of Measure	Average Test Value	Uncertainty Value	Relative Uncertainty
Energy Output	kW			
Chiller Total Input Power	kW	2906	±22	±0.74%
Summary of Test Results				
	Units of Measure	Average Test Value	Uncertainty Value	Relative Uncertainty
Evaporator Net Capacity	tonR	292500	±12000	±4.2%
Condenser Net Capacity	tonR	334800	±16000	±4.7%
Chiller Total Input Power	kW	2906	±22	±0.74%
Cooling Energy Efficiency	kW/tonR	0.009934	±0.00043	±4.3%
Heating Energy Efficiency	COP	405.1	±22	±5.4%
Evaporator Gross Capacity	tonR	293200	±12000	±4.3%
Condenser Gross Capacity	tonR	333700	±16000	±4.8%
Refrigerant Work Input	kW	2906	±22	±0.74%
Energy Balance	%	-12.6%	±6.4%	±51%

Typically:

- Evaporator
- Condenser
- Input power
- Heat balance

...and the performance summary



# Conclusion

- Field performance testing of chiller cannot be defined like factory chiller testing since the test environment is not controlled.
- ASHRAE Standard 184 covers field performance testing of chillers along with provision for the related influences & issues.
- Standard 184 now includes a workbook to embody the methods and testing covered in the standard.
  - Currently covers water cooled electrically powered chillers.
  - Other types to follow....
- Reminder: It is necessary to identify the objectives between all parties prior to conducting any measurements.
  - Embodied in the Pre-Test calculation.

# Bibliography

- ASHRAE Standard 184, Method of Test for Field Performance of Liquid Chilling Systems



# Questions?



Ian Spanswick  
[ian.spanswick@o2rc.com](mailto:ian.spanswick@o2rc.com)